



QUOTE FORM FOR RAMA® BAND HEATER

INQUIRY DATE: \_\_\_\_\_ QTY: \_\_\_\_\_
COMPANY: \_\_\_\_\_ CONTACT NAME: \_\_\_\_\_
ADDRESS: \_\_\_\_\_ CITY: \_\_\_\_\_ STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_
PHONE: \_\_\_\_\_ E-MAIL: \_\_\_\_\_

SPECIFICATIONS:

INNER DIAMETER: \_\_\_\_\_ (OUTER DIAMETER OF PART HEATER IS TO GO ON)
WIDTH: \_\_\_\_\_ (LENGTH OF THE AREA ON THE PART HEATER IS TO COVER)
WATTS: \_\_\_\_\_ VOLTS: \_\_\_\_\_
PHASE: [ ] SINGLE [ ] 3-PHASE (WYE ONLY) [ ] DUAL \_\_\_\_/\_\_\_\_ (ENTER BOTH HIGH & LOW VOLTAGES)
OPERATING TEMPERATURE: \_\_\_\_\_ °F
(IF NOT GIVEN WE WILL DESIGN FOR VALUES BEING AT STARTUP TEMPERATURES OF 68°F)

CONFIGURATION:

LEAD TYPE: [ ] TYPE 'A' [ ] TYPE 'B' [ ] TYPE 'C' [ ] TYPE 'D' [ ] TYPE 'E' [ ] TYPE 'F' [ ] TYPE 'G' [ ] TYPE 'H' [ ] TYPE 'J'
IF CHOOSING LEADWIRE, PROVIDE FINISHED LENGTH: \_\_\_\_\_ ±2%
POST TERMINALS: [ ] TYPE 'K' [ ] TYPE 'L' [ ] TYPE 'M'

DESIGN FEATURES:

SHEATH MATERIAL: [ ] ALUMINIZED STEEL (STANDARD) [ ] STAINLESS STEEL
GAP: [ ] 1/4" (STANDARD) [ ] SPECIAL \_\_\_\_\_ (ENTER GAP SIZE)
MODIFICATION: [ ] BENDABLE [ ] TWO PIECE \_\_\_\_/\_\_\_\_ (ENTER VOLTAGES FOR EACH HALF)
CLAMP: [ ] STRAP [ ] 90° FACING [ ] PIN & SCREW
TEMPERATURE CONTROL: [ ] THERMOCOUPLE [ ] THERMOSTAT
A DRAWING MUST BE SUBMITTED FOR SPECIAL HOLES, CUTOUTS, UNUSUAL SHAPES, THERMOSTAT PLACEMENT, THERMOCOUPLE PLACEMENT, ETC. CONSULT FACTORY FOR STRIP HEATERS OVER 45" LONG OR 12" WIDE.

NOTE ANY SPECIAL REQUIREMENTS BELOW:

Five horizontal lines for writing special requirements.