



RAMA CORPORATION

QUOTE FORM FOR RAMA® ROD AND EDM® CARTRIDGE HEATER

INQUIRY DATE: _____ QTY: _____

COMPANY: _____ CONTACT NAME: _____

ADDRESS: _____ CITY: _____ STATE: _____ ZIP: _____

PHONE: _____ E-MAIL: _____

SPECIFICATIONS:

VOLTS: _____ WATTS: _____ WATT DENSITY: _____ MAX TEMP (°F) _____

DIAMETER STANDARD: NOMINAL (ACTUAL) 1/4 (.245) 3/8 (.370) 1/2 (.495) 5/8 (.620) 3/4 (.745)

DIAMETER METRIC: NOMINAL (ACTUAL) 6.5 (.255) 8 (.315) 10 (.394) 12.5 (.492) 16 (.630) 20 (.787)

SHEATH LENGTH: _____ ±2% SHEATH MATERIAL: INCOLOY STAINLESS STEEL

TOTAL HEATED LENGTH: _____ ±2% (MIN .25" COLD AREA REQUIRED AT LEAD END)

HEAT: STANDARD PROFILED IF PROFILED PROVIDE WATTAGE PER ZONE: _____/_____/_____

MULTICIRCUIT: 3-PHASE 2-ZONE 3-ZONE (NOTE: FOR 3/4" ONLY. MINIMUM LENGTH REQUIRED)

STANDARD CONFIGURATIONS AND MODIFICATIONS:

CONFIGURATIONS AND MODIFICATIONS MAY BE VIEWED ON OUR WEBSITE. CHOOSE FROM THE FOLLOWING LISTED:

- TYPE 'A' TYPE 'B' TYPE 'C' TYPE 'CE' TYPE 'D' TYPE 'E' TYPE 'F' TYPE 'G' TYPE 'H' TYPE 'I'
- TYPE 'HR' TYPE 'J' TYPE 'K' TYPE 'L' TYPE 'N' TYPE 'Q' TYPE 'S' TYPE 'U' TYPE 'U' TYPE 'W'

TYPE 'A' HEATERS MAY BE MODIFIED FROM STOCK IF AVAILABLE. CHOOSE FROM THE FOLLOWING LIST BELOW:

- MOD 'E' MOD 'G' TYPE 'G' TYPE 'L' TYPE 'S'

TERMINATION:

LEADWIRE LENGTH: _____ ±2% LEADWIRE TYPE: FIBERGLASS TEFLON CORD (SPECIAL)

THERMOCOUPLE LENGTH: _____ ±2% TYPE 'J' (STANDARD) TYPE 'K' OTHER

ARMOR LENGTH: _____ ±2% Si/FIBER SLEEVE S/S BRAID S/S CONDUIT CERAMIC BEAD

SPECIAL SEALANT: RAMA CAN PROVIDE SPECIAL EPOXY SEALS, SILICONE VARNISH, OR RTV UPON REQUEST

SPECIAL ITEMS: GROUND WIRE, POST TERMINAL, TWIST LOCK PLUGS, THERMOSTATS, COOLING FINS, AND OTHER ACCESSORIES MAY BE AVAILABLE UPON REQUEST. CONSULT FACTORY FOR SPECIFICATIONS.

SPECIAL NON-STANDARD DESIGNS MUST BE ACCOMPANIED BY A DIMENSIONAL DRAWING.

NOTE ANY SPECIAL REQUIREMENTS BELOW:
