



**QUOTE FORM FOR RAMA®FLEX HEATER**

INQUIRY DATE: \_\_\_\_\_ QTY: \_\_\_\_\_  
COMPANY: \_\_\_\_\_ CONTACT NAME: \_\_\_\_\_  
ADDRESS: \_\_\_\_\_ CITY: \_\_\_\_\_ STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_  
PHONE: \_\_\_\_\_ E-MAIL: \_\_\_\_\_

**SPECIFICATIONS:**

WIDTH OR OUTER DIAMETER \_\_\_\_\_ LENGTH OR INNER DIAMETER \_\_\_\_\_  
WATTS: \_\_\_\_\_ VOLTS: \_\_\_\_\_ PHASE:  SINGLE  3-PHASE (WYE)  3-PHASE (DELTA)  DUAL \_\_\_\_\_/\_\_\_\_\_  
(HIGH/LOW)  
OPERATING TEMPERATURE: \_\_\_\_\_ °F (STANDARD DESIGN FOR VALUES AT STARTUP TEMPERATURES ARE 68°F)  
LEADWIRE LENGTH: \_\_\_\_\_ ±2% TYPE:  TEFLON (STANDARD)  SILICONE  HPN CORD  
SILICONE RUBBER COLOR:  RED (STANDARD)  BLACK  OTHER (CONSULT FACTORY)

**DESIGN FEATURES:**

INSULATION THICKNESS (RED ONLY):  NONE  1/8"  1/4"  
GROUND SCREEN:  NONE  ALUMINUM  BRASS  
MOUNTING METHOD:  NOT NEEDED  ADHESIVE  HOOKS & SPRINGS  LACIN EYELETS  VELCRO  VULCANIZED  
THERMOSTAT:  ADJUSTABLE  FIXED \_\_\_\_\_ °F (OPENING TEMPERATURE)  
THERMOCOUPLE:  TYPE 'J' (STANDARD)  TYPE 'K'  TYPE 'T'  
SILK SCREEN ARTWORK MAY AVAILABLE. CONSULT FACTORY FOR DETAILS.

A DRAWING MUST BE SUBMITTED FOR SPECIAL DESIGNS, THERMOSTAT/THERMOCOUPLE PLACEMENT, SILK SCREEN ARTWORK, VULCANIZING PLACEMENT, AND OTHER FEATURES.

**NOTE ANY SPECIAL REQUIREMENTS BELOW:**

---

---

---

---

---

---

---

---