## QUOTE FORM FOR FLANGED AND SCREW-IN IMMERSION HEATER

| INQUIRY DATE:                        |                      |                      |                     |        |
|--------------------------------------|----------------------|----------------------|---------------------|--------|
| COMPANY:                             |                      | CONTACT NAME: _      |                     |        |
| ADDRESS:                             |                      |                      |                     |        |
| PHONE:                               | FAX:                 | E-                   | MAIL:               |        |
|                                      |                      |                      |                     |        |
| SPECFICATIONS:                       |                      |                      |                     |        |
| VOLTS: WATTS:                        | PHASE:               | WATT DENSITY:        | BUSSING TYPE:       |        |
| HEATER ELEMENT:                      |                      |                      | (SERIES OR PARA     | LLEL)  |
| QTY: DIAMETER:                       | MATERIAL:            | MINIMUM BUNDL        | E DIAMETER:         |        |
| MAXIMUM 'B' LENGTH:                  | _SUPPORT RING: YES _ | NO MAXIMUM COL       | D: (MIN 2" COLD REC | QUIRED |
| (A SUPPORT RING IS AUTOMATICAL       | LY ADDED TO EVERY 36 | 6" OF LENGTH)        |                     |        |
|                                      |                      |                      |                     |        |
| FLANGED IMMERSION:                   |                      |                      |                     |        |
| FLANGE SIZE: PRESSUR                 | E CLASS: 150 LB 30   | 00 LB FLANGE MATERIA | AL:                 |        |
| HOUSING ENCLOSURE: DUST RESIST       | TANT WATER RESIS     | STANT EXPLOSION RESI | STANT               |        |
|                                      | 'A' DIM              | 'В' ОІМ —            | -                   |        |
|                                      |                      | — COLD DIM ———       |                     |        |
|                                      |                      | 7700 0111            |                     |        |
|                                      |                      |                      |                     |        |
|                                      |                      |                      | ) 'c' DIM           |        |
|                                      |                      |                      |                     |        |
|                                      |                      |                      |                     |        |
|                                      | → 'D' DIM ←          |                      |                     |        |
| SCREW-IN IMMERSION:                  |                      |                      |                     |        |
| NPT PIPE SIZE: PIPE MA               | ATEDIAL: C           | NDEDATING DDESSLIDE: |                     |        |
|                                      |                      |                      |                     |        |
| ENCLOSURE TYPE: GUA GUAC _           |                      |                      |                     |        |
|                                      | *A' DIM              | 'B' DIM              | -                   |        |
|                                      | →                    | COLD DIM -           |                     |        |
|                                      |                      |                      |                     |        |
|                                      | •                    |                      |                     |        |
|                                      |                      |                      | )) 'c' DIM          |        |
|                                      |                      |                      |                     |        |
|                                      |                      | D                    |                     |        |
|                                      |                      |                      |                     |        |
| OPTIONS:                             |                      |                      |                     |        |
| THERMOWELL: YES NO IF YES            | , DIAMETER LEN       | GTH                  |                     |        |
| INTEGRAL THERMOSTAT: YES N           |                      |                      |                     |        |
| NOTE ANY SPECIAL REQUIREMENTS        |                      |                      |                     |        |
| WOTE / WIT OF ESWAE NEEDS IN ENTERTY | 5220 ***             |                      |                     |        |
|                                      |                      |                      |                     |        |
|                                      |                      |                      |                     |        |
|                                      |                      |                      |                     |        |
|                                      |                      |                      |                     |        |
|                                      |                      |                      |                     |        |