QUOTE FORM FOR RAMA®STRIP HEATER

INQUIRY DATE:	QTY:			
COMPANY:		CONTACT NAM	IE:	
ADDRESS:		_CITY:	STATE:	ZIP:
PHONE:	E-MAIL:			
SPECIFICATIONS:				
LENGTH: WIDTH:	WATTS:	VOLTS:		
PHASE: SINGLE 3-PHASE (WYE				GES)
OPERATING TEMPERATURE:				•
(IF NOT GIVEN WE WILL DESIGN FOR		JP TEMPERATURES	S OF 68°F)	
CONFIGURATION:				
LEAD TYPE: ☐ TYPE 'A' ☐ TYPE 'B'	☐ TYPE 'C' ☐ TYPE 'D'	☐ TYPE 'E' ☐ TYP	E 'F' TYPE 'G' T	YPE 'H' □ TYPE 'J'
IF CHOOSING LEADWIRE, PROVIDE FI	NISHED LENGTH:	±2%		
POST TERMINALS: ☐ TYPE 'K' ☐ TY	PE 'L' ☐ TYPE 'M'			
DESIGN FEATURES:				
SHEATH MATERIAL: ALUMINIZED	STEEL (STANDARD) 🗆 ST	AINLESS STEEL		
MOUNTING SLOTS: ☐ 3/16" X 3/8" (STANDARD) □ NONE □	SPECIAL (DRAWIN	NG REQUIRED)	
TEMPERATURE CONTROL: ☐ THERM	OCOUPLE	TAT		
A DRAWING MUST BE SUBMITED FOR	SPECIAL HOLES, CUTOUT	S, UNUSUAL SHAP	ES, THERMOSTAT PLAC	EMENT,
THERMOCOUPLE PLACEMENT, ETC. C	ONSULT FACTORY FOR ST	RIP HEATERS OVER	: 45" LONG OR 12" WID	DE.
NOTE ANY SPECIAL REQUIREMENTS I	BELOW:			