| INQUIRY DATE: _ | | QTY: | | | |
|-----------------|-------------------------|-----------------------|---------------------|---------------------|--------------------|
| COMPANY: | CONTACT NAME: | | | | |
| ADDRESS: | | | CITY: | STATE: | ZIP: |
| PHONE: | | E-MAIL: _ | | | |
| | | | | | |
| SPECIFICATIONS | : | | | | |
| VOLTS: | WATTS: | WATT DENSITY: | MAX TEMP (° | F) | |
| DIAMETER: □. | 165 🗆 .215 🗆 .245 🗆 | .290 🗆 .315 🗆 .330 | 0 □ .375 □ .440 | □ .490 | |
| MATERIAL: 🗆 I | NCOLOY (.215490) □ S | TAINLESS STEEL (.160- | 490) □ STEEL (.21 | 5490) 🗆 COPPER (| .315490) |
| SHEATH LENGTH | :±2% HEA | TED LENGTH: | ±2% (NOTE: MI | N 1" COLD AREA REQI | JIRED AT EACH END) |
| HEAT: ☐ STAND | ARD □ PROFILED | | | | |
| CLASSIFICATION: | ☐ STRAIGHT ☐ FORM | MED (NOTE: YOU MAY | CHOOSE FROM ONE | OF THE FIGURES ON | OUR WEBSITE |
| OTHERWISE A DE | RAWING MUST BE INCLUE | DED WITH BEND SPECI | FICATIONS) | | |
| STANDARD TERM | //INATION: □ BARE □ T | YPE 'A' □ TYPE 'B' [| ☐ TYPE 'C' ☐ TYPE | 'D' | |
| SPECIAL TERMIN | ATION: □ LEADWIRE □ | BUSHING SILICON | E BOOT □ CERAMI | C-TO-METAL SEAL | |
| SPECIAL SEALAN | T: RAMA CAN PROVIDE SF | PECIAL EPOXY SEALS, S | ILICONE VARNISH, C | OR RTV UPON REQUES | Т |
| | | | | | |
| OTHER ACCESSO | RIES SUCH AS FLANGES, T | ABS, OR HEAT DISSIPA | ATING FINS MAY BE A | ADDED UPON CUSTON | MER REQUEST. |
| | , | , | | | · |
| NOTE ANY SPECIA | AL REQUIREMENTS BELO | W: | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |